UNSTEADY FLOW PHENOMENA IN CENTRIFUGAL TURBOMACHIMERY
(U) MASSACHUSETTS INST OF TECH CAMBRIDGE GAS TURBINE
LAB D R FINK 88 SEP 86 AFOSR-TR-87-8554 AFOSR-84-8343
F/G 20/4

1/1

AD-A179 714

UNCLASSIFIED



AD-A179	714	~~~	atre	FILE	000	
70 7170		IENTATION PAG	E		CUPY	
14 REPORT SECURITY CLASSIFICATION UNCLASSIFIED		16. RESTRICTIVE N	MARKINGS			
26 SECURITY CLASSIFICATION AUTHORITY		3 DISTRIBUTION/AVAILABILITY OF REPORT				
28. DECLASSIFICATION/DOWNGRADING SCHEDULE		APPROVED FOR PUBLIC RELEASE DISTRIBUTION IS UNLIMITED				
4. PERFORMING ORGANIZATION REPORT NUMBER(S)			AFOSR-TR- 87-0554			
MASSACHUSETTS INST OF	E GHappiicable	'. NAME OF MON!	TORING ORGANI NA	ZATION	* · · · · · · · · · · · · · · · · · · ·	
CAMBRIDGE, MASSACHUSET 02139	TES	BOILDI BOLLIN	NG 410 Code		448	
AFOSR/NA Bb OFFICE SYMBOL Ill applicable:		9 PROCUREMENT INSTRUMENTS IDENTIFICATION NUMBER				
e. ADDRESS (C. U. Siele pad ZIP Code) BUILDING 410			10 SOURCE OF FUNDING NOS			
BOLLING AFB, DC 20332-	-6448	PROGRAM ELEMENT NO 61102E	PROJECT NO. 2 2227 2917	TASK NO. Al	WORK UNIT	
(U) UNSTEADY FLOW PHEN	NOMENA IN CEN	TRIFUGAL TUE	BOMACHINE	RY		
12. PERSONAL PANTHORIS	<u></u>	····	 			
134 TYPE OF REPORT 136. TIME COVERED FINAL		14 DATE OF SEP	BT Ne. Mo. Deyi	15. PAGE	COUNT	
16. SUPPLEMENTARY NOTATION	†o	-1				
17. COSATI CODES	18 SUBJECT TERMS	Continue on reverse if no	ccessary and identif	y by block numb	er)	
FIELD GROUP - SUB GR	CENTRIFUGAL COMPRESSORS, UNSTEADY TURBOMACHINERY TURBOMACHINERY					
This grant supported a research program supported stall to investigate sinstabilities in a cer	an AFRAPT tra orted by Cumm system dynami	inee in conj ins Engine (cs, unsteady	Company or	and deta	arger iled flow	
26. DISTRIBUTION/AVAILABILITY OF ASSTRA		21 ABSTRACT SECURITY CLASSIFICATION				
UNCLASSIFIED/UNLIMITED AND AS APT	UNCLAS	SSIFIED 				
HENRY E HELIN, CAPTAIN, USAF		226 TELEPHONE N Include tree Co 202-76	UMBER 0007-4935	22c OFFICE SY	MBOL AFOSR/NA	

EDITION OF 1 JAN 73 IS OBSOLETE

GAS TURBINE LABORATORY

DEPARTMENT OF AERONAUTICS AND ASTRONAUTICS

MASSACHUSETTS INSTITUTE OF TECHNOLOGY

CAMBRIDGE, MASSACHUSETTS 02139

EDWARD M. GREITZER

PROFESSOR AND DIRECTOR

September 8, 1986

AFOSR-TR- 87-0554

AFOSR/PKD Building 410 Bolling AFB, DC 20332-6448

Attn: Anne G. Sprunt

Subject: Final Technical Report AFOSR-84-0343

Dear Ms. Sprunt:

This is a letter report covering the work done under the AFRAPT program during the period 9/1/84-8/31/85 on the topic of Unsteady Flow Phenomena in Centrifugal Turbomachinery. The work was supported by Grant AFOSR-84-0343.

This grant was established solely for the support of an AFRAPT trainee, David A. Fink in conjunction with an ongoing research program supported by Cummins Engine Company on Turbocharger Stall.

The research is an experimental investigation of system dynamics, unsteady effects, and detailed flow instabilities in a centrifugal compressor. The surge line, which marks the onset of instability and hence limits the minimum stable operating regime, is a primary design constraint in matching the compressor to downstream turbine and combustor (gas turbine gas generator) or diesel engine (turbocharger). The ultimate goal of this research is a thorough understanding of the events occurring in the compression system which cause surge. The first portion of the research dealing with facility development and initial unsteady data was documented in the S.M. thesis of Mr. Fink in May 1984.

The work for the Ph.D. thesis concentrates on time-resolved measurement of compressor parameters (static pressures, massflow, speed, and temperature) during surge. Time-resolved compressor parameter data taken recently during deep surge operation is shown in Figure 1. Most notable, as shown in the upper trace, is the relatively slow growth in massflow instability prior to flow reversal, which gives encouragement to prospects for attenuation or elimination of these oscillations by active control. The second trace in Figure 1 shows the instantaneous system parameter B during deep surge. This system parameter which governs the post-stall behavior of axial compressor has been found to be a major parameter in the surge behavior of centrifugal compressors. During the approach to flow reversal, the B-parameter is found to be increasing due to increasing rotor speed. At a critical value of B, the compressor massflow reverses.

The B-parameter determines the major placement of the surge line. As B is reduced by decreasing compressor speed or downstream volume for example, the surge line is shifted favorably to the left and the system should operate stably to nearly shutoff conditions. Use of a small B system would allow measurement of low flow compressor characteristics which are inaccessible in most practical compressor installations. The curvature of these characteristics as well as the detailed fluid dynamic processes (diffuser and impeller stall) which determine their shape is most important in modelling surge behavior and is currently being explored in the most recent work of Mr. Fink. The data consists of both time resolved and time averaged measurements. The results of these experiments will appear in Mr. Fink's Ph.D. thesis in Spring 1987.

Please let me know if any further information is needed.

Sincerely,

Edward M. Stretzer

Edward M. Greitzer

Enclosure

cc: Dr. McMichael/NA

Mr. J.G. Mahoney, OSP 95420

Ms. H.E. Rathbun

EMG/dm

Access	ion For	
NTIS DTIC 1 Unanno Justii	AB 2	
By Distri	bution/	Charles C
Avail	lability Code	5
	Avail and/or Special	
A-1		




FIGURE 1

Gopy available to DTIC does not permit fully legible seprodection